

PP 803 Professional Dot Matrix Printer for Industry, Logistics and Administration



PP 803 with optional 2nd Tractor Cassette and Printer Stand

- Heavy duty 24-wire dot matrix printer with Intellidrive™ - Technology
- Compact flat bed design with print bar, 92 col.
- Performance:
 - 600 cps (10 cpi)
 - 500 pages/hour
 - 40.000 pages/month
- Up to 9 copies (1+8)
- Precise print registration
- Easy user operation via macro functions
- Low cost per page through 15 Mio character ribbon
- Optional paper cutter
- Personality Modules (interfaces) for major host and network environments

The PP 803 printer offers a professional solution for heavy duty, flexible, cost-efficient printing. The rugged metal design, the paper run control, and the ribbon run control guarantee reliable unattended printing. With its proven connectivity concept the PP 803 is prepared for any network environment.

The ultra precise registration allows perfectly to fill-in pre-printed forms such as shipping documents and tickets. The Intellidrive™ - Technology guarantees a perfect print quality with crisp letters and barcodes with highest readability. The Automatic Gap Control (AGC) allows to print on paper up to 1mm (0.04 inch) thickness and transport paper with a thickness up to 2 mm (0.08 inch). The long-life print head fires the wires against a print bar and can produce up to 9 copies.

Up to two Tractor Cassettes and the Auto-Tear-off function make the handling of fanfold paper as easy as possible.

TECHNICAL DATA

Printer Specification

Technology:	serial impact dot matrix
Printhead:	24 wires, 0.25 mm needle diameter; life time 400 million characters (DQ)
Print mode:	high speed draft (HSD), data (DQ), near letter (NLQ) and letter quality (LQ)
Print format:	92 characters at 10 cpi
Ribbon:	cartridge nylon ribbon black, 15 million characters, auto ribbon run control
Dimensions:	550 x 280 x 295 mm (WxDxH) (21.7 x 11.0 x 11.3 inch)
Weight:	15.7 kg (34 lb)
Diagnostics:	selftest, hexdump, remote diagnostics via interface
Operator Panel:	16 digit LCD display, trilingual (German, English, French)
Keyboard:	Membrane tactile type with Ready/Stop LED
Rated voltage:	100 - 125 VAC / 200 - 240 VAC 3A / 1.5A 50 - 60 Hz
Power input:	operating approx. 200 W, 30 W Standby
Environmental temperature:	operating: +10 to +35 °C (+50 to + 95°F) 20 to 80% rel. humidity storage: -40 to +70 °C (-40 to +158°F) 5 to 85% rel. humidity approx. 53 dB(A) acc. to ISO 7779
Noise level:	
Agency approvals:	VDE/GS, UL, CE, FCC-B

Performance

Print speed:	DQ: 600 cps at 10 cpi NLQ: 300 cps at 10 cpi LQ: 150 cps at 10 cpi
Throughput:	DQ: 500 pages/hour
Duty cycle:	40,000 pages per month
MTBF:	15,000 hours at 30% duty cycle

Paper Handling

Paper path:	flatbed design; 2 paper inputs, 1 output for fanfold paper, paper path selectable via software or operator panel
Paper input:	one removable tractor cassette, slot for optional second tractor cassette
Paper output:	to the rear with zero tear-off
Paper weight:	60 to 150 g/m ² formsets up to 480 g/m ²
Paper width:	105 to 270 mm (4 to 10.625 inch)
Form feed:	20 inch/second;
Automatic Gap Control (AGC):	optimizes automatically the print gap according to paper thickness
Copies:	1 original + 8 copies; max. paper thickness 1.0 mm (0.04 inch), 2.0 mm (0.08 inch) transportation

Connectivity

PERSONALITY MODULE SER/PAR (Option)

Interfaces:	parallel Centronics and serial RS-232C/RS422, shared mode
Emulations:	IBM Proprinter XL24 (AGM), Epson LQ 2550/1060/ESC/P2
Buffer:	up to 64 KByte
Character sets:	ISO 8859/1, ISO 8859/15; IBM Set 1/Set 2 in 14 national versions; IBM Code Pages 437, 850, 858, 860, 863, 865; Epson Ext. Char. Set in 15 national versions; Eastern European character sets optional
Fonts:	draft quality: High Speed Draft, Data and Data Large; Near letter and letter quality: Courier, Sans Serif, OCR-A, OCR-B, Orator, Orator-C, Prestige, Roman, and Script
Character attributes:	bold, italic, shadow, outline, double strike, underline, double underline, overline, strike through, sub/ superscript, double to octuple, for Data Large 99-fold size
Pitches:	10, 12, 15, 17.1, 18 and 20 cpi, proportional
Line spacing:	2, 3, 4, 6, 8, ... 360 lpi
Barcode:	EAN 8, EAN 13, UPC-A, UPC-E, Postnet, KIX Code, Code 39, Code 93, Code 128 (incl. EAN 128), Codabar, 2 of 5 industrial, 2 of 5 interleaved, and MSI Mod 10/10
Graphics:	360 x 360 dpi max.
Macros:	parameter settings for up to four individual printer configurations, selectable via software or Operator panel

Other optional PERSONALITY MODULES

Ethernet:	Ethernet 10BaseT / 100BaseTX RJE45
Twinax IPDS:	IBM Twinax and parallel
IGP:	SER/PAR PM with Printronix IGP 10/20/40 emulation
HP:	SER/PAR or Ethernet PM with HP2934/2235 emulations
WLAN:	Wireless LAN according IEEE 802.11b, 11 MBit/s WEP Security, EPSON LQ- and IBM Proprinter Emulation, Europe only

Printer drivers for Windows 3.x/95/98/NT 4.0 /2000/XP are available. SAP R/3 device types are available for download at www.psiprinters.com.

Options

Printer stand:	for handling of dual fanfold paper input, dimensions: (WxDxH) 450 x 660 x 840 mm (17.7 x 26.4 x 33.6 inch); weight: approx. 16 kg (43.5 lb)
Tractor cassettes:	Enables auto loading of second form. Extra cassettes may be dedicated to regularly used forms for quick loading.
Cutter:	Internal cutting device enables forms to be separated. Panel setting allows automatic cut between print jobs.
Collector Trays:	Trays attach to printer and collect individual sheet output - Front or Rear.
Manual feed unit:	for single sheet or formset input.
Interface:	Personality Modules

This is only an extract of the product specification. For a detailed specification it is referred to the comprehensive product documentation. Specifications are subject to change without notice. All registered trademarks are the property of their respective companies.